Amendment under 37 C.F.R. § 1.114 U.S. Application No.: 09/236,897

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (Currently Amended) A chemical analysis system comprising:

a means for spotting a sample liquid onto a first chemical analysis element for measuring the concentration of a specific component contained in the sample liquid,

a means for spotting a sample liquid and a reference liquid onto a second chemical analysis element for measuring the activity of a specific ion contained in the sample liquid,

an incubator in which the first chemical analysis element spotted with the sample liquid and the second chemical analysis element spotted with the sample liquid and the reference liquid are placed and which <u>automatically</u> holds the first and second chemical analysis elements at constant temperatures,

a concentration measuring means which is provided to measure the concentration of the specific component contained in the sample liquid by measuring the optical density of the color formed by the coloring reaction of the sample liquid and a reagent on the first chemical analysis element after incubation in the incubator,

an ionic activity measuring means which is provided to measure the ionic activity of the specific ion contained in the sample liquid after incubation in the incubator,

a temperature control means which for automatically holdings the first and second chemical analysis elements at predetermined temperatures, and

a detector comprising a bar code reading means er for detecting the position of the chemical analysis element in which the chemical analysis element is conveyed by reading a bar code provided on each chemical analysis element.

2. (Original) A chemical analysis system as defined in Claim 1, further provided with a chemical analysis element supply section which stores both the first and the second chemical

Amendment under 37 C.F.R. § 1.114 Attorney Docket No.: Q53086

U.S. Application No.: 09/236,897

analysis elements, and a conveyor means for conveying the chemical analysis element in the chemical analysis element supply section to the incubator.

3. (Canceled).

4. (Original) A chemical analysis system as defined in Claim 1 further provided with a diluting unit which includes a sample liquid contained and dilutes the sample liquid in the container with diluent.

5. (Currently Amended) A chemical analysis system comprising:

a means for spotting a sample liquid onto a first chemical analysis element for measuring the concentration of a specific component contained in the sample liquid,

a means for spotting a sample liquid and a reference liquid onto a second chemical analysis element for measuring the activity of a specific ion contained in the sample liquid,

an incubator in which the first chemical analysis element spotted with the sample liquid and/or the second chemical analysis element spotted with the sample liquid and the reference liquid are placed and which holds the first and/or second chemical analysis elements at constant temperatures,

a concentration measuring means which is provided to measure the concentration of the specific component contained in the sample liquid by measuring the optical density of the color formed by the coloring reaction of the sample liquid and a reagent on the first chemical analysis element after incubation in the incubator,

an ionic activity measuring means which is provided to measure the ionic activity of the specific ion contained in the sample liquid after incubation in the incubator, and

a temperature control means which for automatically maintaining holds the first chemical analysis element at a first predetermined temperature suitable for measuring the optical density of the color formed by the coloring reaction and holds the second chemical analysis elements at a second predetermined temperatures suitable for measuring ionic activity. 3 and

Amendment under 37 C.F.R. § 1.114 Attorney Docket No.: Q53086

U.S. Application No.: 09/236,897

a detector comprising a bar code reader for detecting the position of the chemical analysis

element in which the chemical analysis element is conveyed by reading a bar code provided on

each chemical analysis element.

6. (Original) A chemical analysis system as defined in Claim 5 further provided with a

chemical analysis element supply section which stores both the first and second chemical

analysis elements, and a conveyor means for conveying the chemical analysis element in the

chemical analysis element supply section to the incubator.

7. (Canceled).

8. (Original) A chemical analysis system as defined in Claim 5 further provided with a

diluting unit which includes a sample liquid container and dilutes the sample liquid in the

container with diluent.

9. (Currently Amended) A chemical analysis system, comprising:

a spotting mechanism operable to spot a sample liquid onto a first chemical analysis

element for measuring the concentration of a specific component contained in the sample liquid,

and operable to spot a sample liquid and a reference liquid onto a second chemical analysis

element for measuring the activity of a specific ion contained in the sample liquid;

an incubator in which the first chemical analysis element spotted with the sample liquid

and the second chemical analysis element spotted with the sample liquid and the reference liquid

are placed and which holds the first and second chemical analysis elements at constant

temperatures;

a concentration measuring device operable to measure the concentration of the specific

component contained in the sample liquid by measuring the optical density of the color formed

by the coloring reaction of the sample liquid and a reagent on the first chemical analysis element

after incubation in the incubator;

4

Amendment under 37 C.F.R. § 1.114 U.S. Application No.: 09/236,897

an ionic activity measuring device operable to measure the ionic activity of the specific ion contained in the sample liquid after incubation in the incubator;

a temperature control device <u>comprising a temperature control element and a first</u> <u>pressing member for the first chemical analysis element and a second pressing member for the second chemical analysis element, the temperature control device which holds the first and second chemical analysis elements at predetermined temperatures; and</u>

a detector comprising a bar code reader for detecting the position of the chemical analysis element in which the chemical analysis element is conveyed by reading a bar code provided on each chemical analysis element.

- 10. (Previously Presented) A chemical analysis system as defined in claim 1, further provided with a receiving portion located in the incubator which stores a single chemical analysis element.
- 11. (Previously Presented) A chemical analysis system as defined in claim 10, further provided with a plurality of the receiving portions, which are located in the incubator, each for storing a chemical analysis element wherein the incubator is capable of simultaneously maintaining different temperatures in the different receiving portions.
- 12. (Previously Presented) A chemical analysis system as defined in claim 10, wherein the incubator is capable of simultaneously maintaining different temperatures for the first chemical analysis element and for the second chemical analysis element.
- 13. (Previously Presented) A chemical analysis system as defined in claim 5, further provided with a receiving portion located in the incubator which stores a single chemical analysis element.
- 14. (Previously Presented) A chemical analysis system as defined in claim 13, further provided with a plurality of the receiving portions, which are located in the incubator, each for

Amendment under 37 C.F.R. § 1.114 U.S. Application No.: 09/236,897

storing a chemical analysis element wherein the incubator is capable of simultaneously maintaining different temperatures in the different receiving portions.

- 15. (Previously Presented) A chemical analysis system as defined in claim 13, wherein the incubator is capable of simultaneously maintaining different temperatures for the first chemical analysis element and for the second chemical analysis element.
- 16. (Currently Amended) A chemical analysis system comprising:

means for spotting a sample liquid onto a first chemical analysis element for measuring the concentration of a specific component contained in the sample liquid,

means for spotting a sample liquid and a reference liquid onto a second chemical analysis element for measuring the activity of a specific ion contained in the sample liquid,

an incubator capable of simultaneously maintaining two different temperatures for simultaneously holding the first chemical analysis element spotted with the sample liquid and the second chemical analysis element spotted with the sample liquid and the reference liquid,

a concentration measuring means which is provided to measure the concentration of the specific component contained in the sample liquid by measuring the optical density of the color formed by the coloring reaction of the sample liquid and a reagent on the first chemical analysis element after incubation in the incubator,

an ionic activity measuring means which is provided to measure the ionic activity of the specific ion contained in the sample liquid after incubation in the incubator, and

a temperature control means <u>for which</u> hold<u>ing</u> s the first chemical analysis element at a first predetermined temperature suitable for measuring the optical density of the color formed by the coloring reaction and holds the second chemical analysis element at a second predetermined temperature suitable for measuring the ionic activity.

17. (Previously Presented) A chemical analysis system as defined in claim 16, further provided with a receiving portion located in the incubator which stores a single chemical analysis element.

Amendment under 37 C.F.R. § 1.114 U.S. Application No.: 09/236,897

18. (Previously Presented) A chemical analysis system as defined in claim 17, further provided with a plurality of the receiving portions, which are located in the incubator, each for storing a chemical analysis element wherein the incubator is capable of simultaneously maintaining different temperatures in the different receiving portions.

- 19. (Previously Presented) A chemical analysis system as defined in claim 16, wherein the incubator is capable of simultaneously maintaining the temperature of about 37°C at the receiving portion for storing the first chemical analysis element and the temperature of 30 °C at the receiving portion for the second chemical analysis element.
- 20. (Previously Presented) A chemical analysis system as defined in claim 16, further provided with a detector comprising a bar code reader for detecting the position of the chemical analysis element in which the chemical analysis element is conveyed by reading a bar code provided on the back of each chemical analysis element.

21. (Currently Amended) A chemical analysis system comprising:

a means for spotting a sample liquid onto a first chemical analysis element for measuring the concentration of a specific component contained in the sample liquid,

a means for spotting a sample liquid and a reference liquid onto a second chemical analysis element for measuring the activity of a specific ion contained in the sample liquid,

an incubator in which the first chemical analysis element spotted with the sample liquid and the second chemical analysis element spotted with the sample liquid and the reference liquid are placed and which holds the first and second chemical analysis elements at constant temperatures,

a concentration measuring means which is provided to measure the concentration of the specific component contained in the sample liquid by measuring the optical density of the color formed by the coloring reaction of the sample liquid and a reagent on the first chemical analysis element after incubation in the incubator,

Amendment under 37 C.F.R. § 1.114 U.S. Application No.: 09/236,897

an ionic activity measuring means which is provided to measure the ionic activity of the specific ion contained in the sample liquid after incubation in the incubator,

a temperature control means which holds the first and second chemical analysis elements at predetermined temperatures, and

means for <u>automatically</u> inserting the first and second chemical analysis elements into given positions in the incubator according to type of chemical analysis element, <u>and</u>

a temperature control means for holding the first and second chemical analysis elements at predetermined temperatures based on the inserted position.

22. (Currently Amended) A chemical analysis system comprising

a means for spotting a sample liquid onto a first chemical analysis element for measuring the concentration of a specific component contained in the sample liquid,

a means for spotting a sample liquid and a reference liquid onto a second chemical analysis element for measuring the activity of a specific ion contained in the sample liquid,

an incubator in which the first chemical analysis element spotted with the sample liquid and/or the second chemical analysis element spotted with the sample liquid and the reference liquid are placed and which holds the first and/or second chemical analysis elements at constant temperatures,

a concentration measuring means which is provided to measure the concentration of the specific component contained in the sample liquid by measuring the optical density of the color formed by the coloring reaction of the sample liquid and a reagent on the first chemical analysis element after incubation in the incubator,

an ionic activity measuring means which is provided to measure the ionic activity of the specific ion contained in the sample liquid after incubation in the incubator,

a temperature control means which holds the first chemical analysis element at a first predetermined temperature suitable for measuring the optical density of the color formed by the coloring reaction and holds the second chemical analysis elements at a second predetermined temperatures suitable for measuring ionic activity, and

Amendment under 37 C.F.R. § 1.114 U.S. Application No.: 09/236,897

means for inserting the first and second chemical analysis elements into given positions in the incubator according to type of chemical analysis element,

wherein the given positions have different pressing members for maintaining the first and the second chemical analysis elements at different temperatures.

23. (Currently Amended) A chemical analysis system, comprising:

a spotting mechanism operable to spot a sample liquid onto a first chemical analysis element for measuring the concentration of a specific component contained in the sample liquid, and operable to spot a sample liquid and a reference liquid onto a second chemical analysis element for measuring the activity of a specific ion contained in the sample liquid;

an incubator in which the first chemical analysis element spotted with the sample liquid and the second chemical analysis element spotted with the sample liquid and the reference liquid are placed and which holds the first and second chemical analysis elements at constant temperatures;

a concentration measuring device operable to measure the concentration of the specific component contained in the sample liquid by measuring the optical density of the color formed by the coloring reaction of the sample liquid and a reagent on the first chemical analysis element after incubation in the incubator;

an ionic activity measuring device operable to measure the ionic activity of the specific ion contained in the sample liquid after incubation in the incubator;

a temperature control device which holds the first and second chemical analysis elements at predetermined temperatures; and

means for inserting the first and second chemical analysis elements into given positions in the incubator according to type of chemical analysis element,

wherein the given positions determine the predetermined different temperatures at which the first and the second chemical analysis elements are held.

Amendment under 37 C.F.R. § 1.114 U.S. Application No.: 09/236,897

24. (New) A chemical analysis system as defined in claim 9, wherein the first pressing member is different in shape from the second pressing member.

25. (New) A chemical analysis system comprising:

means for spotting a sample liquid onto a first chemical analysis element for measuring a first chemical property of the sample liquid;

a means for spotting a sample liquid onto a second chemical analysis element for measuring a second chemical property of the sample liquid, which is different from the first chemical property;

an incubator for holding the first chemical analysis element spotted with the sample liquid and the second chemical analysis element spotted with the sample liquid, wherein the incubator holds the first and the second chemical analysis elements at a constant temperature or at different constant temperatures;

a first measuring means for measuring the first chemical property of the first chemical analysis element, the first measuring means being provided in the incubator;

a second measuring means for measuring the second chemical property of the second chemical analysis element, the second measuring means being provided in the incubator; and

a temperature control means which holds the first and second chemical analysis elements at a predetermined temperature or at predetermined different temperatures.

26. (New) The chemical analysis system according to claim 25, wherein:

Amendment under 37 C.F.R. § 1.114 U.S. Application No.: 09/236,897

the first chemical property is concentration of a specific component contained in the sample liquid;

said first measuring means is a concentration measuring means for measuring the concentration of the specific component contained in the sample liquid by measuring optical density of a color formed by a coloring reaction of the sample liquid and a reagent on the first chemical analysis element after incubation;

the second chemical property is ionic activity of a specific ion contained in the sample liquid;

the second measuring means is an ionic activity measuring means for measuring the ionic activity of the specific ion contained in the sample liquid after incubation; and

further comprising a temperature control means for holding the first and the second chemical analysis elements at predetermined temperatures.

- 27. (New) The chemical analysis system according to claim 26, further comprising a chemical analysis element supply section for storing both the first and second chemical analysis elements, and a conveyor means for conveying the first and the second chemical analysis elements in the chemical analysis element supply section to the incubator.
- 28. (New) The chemical analysis system according to claim 25, further comprising a detecting means for detecting the position of the chemical analysis elements by reading a bar code provided on each of the chemical analysis elements.

Amendment under 37 C.F.R. § 1.114 U.S. Application No.: 09/236,897

29. (New) The chemical analysis system according to claim 25, further comprising a diluting unit, wherein the diluting unit comprises a sample liquid container and dilutes sample liquid in the container with diluent.

30. (New) A chemical analysis system comprising:

means for spotting a sample liquid onto a first chemical analysis element for measuring concentration of a specific component contained in the sample liquid;

a means for spotting the sample liquid onto a second chemical analysis element for measuring activity of a specific ion contained in the sample liquid;

an incubator in which there is placed the first chemical analysis element spotted with the sample liquid, the second chemical analysis element spotted with the sample liquid, and a reference liquid, wherein the incubator holds the first and the second chemical analysis elements at constant temperatures;

a concentration measuring means for measuring the concentration of the specific component contained in the sample liquid on the first chemical analysis element, which is provided in the incubator, by measuring the optical density of color formed by a coloring reaction of the sample liquid and a reagent on the first chemical analysis element;

an ionic activity measuring means for measuring the ionic activity of the specific ion contained in the sample liquid on the second chemical analysis element, which is provided in the incubator; and

a temperature control means for holding the first chemical analysis element at a first predetermined temperature suitable for measuring the optical density of the color formed by the

Amendment under 37 C.F.R. § 1.114 Attorney Docket No.: Q53086

U.S. Application No.: 09/236,897

coloring reaction and for holding the second chemical analysis element at a second predetermined temperature suitable for measuring the ionic activity.

chemical analysis element supply section to the incubator.

31. (New) The chemical analysis system according to claim 30, further comprising a chemical analysis element supply section which stores both the first and the second chemical analysis elements, and a conveyor means for conveying the chemical analysis elements from the

- 32. (New) The chemical analysis system according to claim 30, further comprising a detecting means for detecting the position of the chemical analysis elements by reading a bar code provided on each of the chemical analysis elements.
- 33. (New) The chemical analysis system according to claim 30, further comprising a diluting unit, wherein the diluting unit comprises a sample liquid container and dilutes a sample liquid in the container with diluent.

13